

Centrali a larga banda - Meccanica in pressofusione

Wide band TV Head-ends - Die-casting mechanics

Black Line



LTEfree™

- Amplificatori a larga banda versatili e potenti, interamente schermati con connettori F e telealimentazione 12 V attivabile tramite dip switch.
- Da 1 a 5 ingressi di banda con regolazioni in ingresso tramite attenuatori da 0...20 dB
- Guadagno lineare fino a 40 dB, livello di uscita da 120 a 123 dB μ V con amplificazione separata VHF e UHF.
- Meccanica in pressofusione e alimentatore switching separato per una migliore dissipazione del calore.
- Alimentazione stabilizzata con regolatore di tensione e protezione al corto circuito.

Accessori per la serie "Black Line"

80275A: Alimentatore switching

- Versatile and powerful wide band amplifiers, fully screened with F connectors and equipped with Dip Switch for remote power supply selection independent on each output (12V).
- From 1 to 5 band inputs adjustable by attenuators from 0 to 20 dB.
- Gain up to 40 dB output level from 120 to 123 dB μ V with separated VHF and UHF amplification.
- Die-casting mechanics and separated switching power supply for a better heat dissipation.
- Stabilized power supply with voltage regulator and short circuit protection.

Unit parts for series "Black Line"

80275A: Switching Power Supply

codice code	ingressi In.	bande bands	guadagno gain VHF/UHF	livello uscita output level dB μ V	reg. adj. dB	fig. rumore noise figure V/U dB	uscite outputs n°	alimentazione power supply	consumo consumption
82252L	4	B.III B.IV B.V UHF	30 / 37 dB	115 / 120	20	3 / 7	1	230V ± 10% 50Hz	5.2 W
82254L	3	B.III B.IV B.V	30 / 40 dB	115 / 120	20	3 / 4	1	230V ± 10% 50Hz	5.2 W
82259L	3	B.III UHF UHF	30 / 37 dB	115 / 120	20	3 / 7	1	230V ± 10% 50Hz	5.2 W
82262L	1	Log	30 / 40 dB	115 / 120	20	3 / 4	1	230V ± 10% 50Hz	5.2 W

codice code	ingressi In.	bande bands	guadagno gain VHF/UHF	livello uscita output level dB μ V	reg. adj. dB	fig. rumore noise figure V/U dB	uscite outputs n°	alimentazione power supply	consumo consumption
82300L	1	Log	20 / 20 dB	115 / 123	20	3 / 4	1	230V ± 10% 50Hz	6.8 W
82352L	4	B.III B.IV B.V UHF	30 / 37 dB	115 / 123	20	3 / 7	1	230V ± 10% 50Hz	6.8 W
82372L	4	B.III B.IV B.V UHF	40 / 45 dB	115 / 123	20	3 / 7	1	230V ± 10% 50Hz	6.8 W
82354L	3	B.III B.IV B.V	30 / 40 dB	115 / 123	20	3 / 4	1	230V ± 10% 50Hz	6.8 W
82359L	3	B.III UHF UHF	30 / 37 dB	115 / 123	20	3 / 7	1	230V ± 10% 50Hz	6.8 W
82379L	3	B.III UHF UHF	40 / 45 dB	115 / 123	20	3 / 7	1	230V ± 10% 50Hz	6.8 W
82362L	1	Log	30 / 40 dB	115 / 123	20	3 / 4	1	230V ± 10% 50Hz	6.8 W

codice code	descrizione description
80275A	alimentatore switching per centralini serie "Black Line" / switching power supply for 'Black Line' Series